



Access



Video



Software



Technology



Mirage® Series Proximity Card and Tag

The Mirage® Proximity Cards and Tags are compatible with Sielox's Mirage® and Performa® readers
Pre-programmed customer-specific ID numbers
Available in clamshell or Tag.

AC-15 Series

Sielox's Mirage® Proximity Card contains a passive tuned circuit which absorbs radio frequency (RF) energy transmitted by Performa® or Mirage® readers. This absorbs RF energy then powers a resident integrated circuit. The Mirage® Proximity Cards and Tags operate at 13.56 MHz frequency and are compatible with our Mirage® and Performa® Readers.

The embedded integrated circuit boasts a unique 64 bit key code or electronic signature that is transmitted to the reader via electromagnetic "coupling". This proprietary transmission, undetected by frequency generators or similar devices, provides optimal security and greater protection against counterfeiting.

The functional Mirage® Proximity Tag operates under the same principles as Sielox's Proximity Cards. Because of its smaller size, the Proximity Tag can be carried conveniently on a key ring with no impact or reliability on performance

AC-15-E Mirage Proximity



Dimensions: 3.37" x 2.12" x 0.06"
85.64 mm x 53.85 mm x 1.58 mm

AC-15T-E Mirage Proximity Tag



Dimensions: 2.15" x 1.52" x 0.13"
54.70mm x 38.75 mm x 3.38 mm